

# **RingsForHomalg**

**Dictionaries of external rings**

2023.11-02

4 November 2023

**Mohamed Barakat**

**Simon Görtzen**

**Markus Kirschmer**

**Markus Lange-Hegermann**

**Oleksandr Motsak**

**Daniel Robertz**

**Hans Schönemann**

**Andreas Steenpaß**

**Vinay Wagh**

**Mohamed Barakat**

Email: [mohamed.barakat@uni-siegen.de](mailto:mohamed.barakat@uni-siegen.de)

Homepage: <https://mohamed-barakat.github.io>

Address: Walter-Flex-Str. 3  
57072 Siegen  
Germany

**Simon Görtzen**

Email: [simon.goertzen@rwth-aachen.de](mailto:simon.goertzen@rwth-aachen.de)

Homepage: <https://www.linkedin.com/in/simongoertzen/>

Address: Simon Görtzen  
Lehrstuhl B fuer Mathematik, RWTH Aachen  
Templergraben 64  
52062 Aachen  
Germany

**Markus Kirschmer**

Email: [markus.kirschmer@math.rwth-aachen.de](mailto:markus.kirschmer@math.rwth-aachen.de)

Homepage: <http://www.math.rwth-aachen.de/~Markus.Kirschmer/>

Address: Markus Kirschmer  
Lehrstuhl D fuer Mathematik, RWTH Aachen  
Templergraben 64  
52062 Aachen  
Germany

**Markus Lange-Hegermann**

Email: [markus.lange-hegermann@hs-owl.de](mailto:markus.lange-hegermann@hs-owl.de)

Homepage: <https://www.th-owl.de/eecs/fachbereich/team/markus-lange-hegermann/>

Address: Markus Lange-Hegermann  
Hochschule Ostwestfalen-Lippe  
Liebigstraße 87  
32657 Lemgo  
Germany

**Oleksandr Motsak**

Email: [motsak@mathematik.uni-kl.de](mailto:motsak@mathematik.uni-kl.de)

Homepage: <http://www.mathematik.uni-kl.de/~motsak/>

Address: Department of Mathematics  
University of Kaiserslautern  
67653 Kaiserslautern  
Germany

**Daniel Robertz**

Email: [daniel@momo.math.rwth-aachen.de](mailto:daniel@momo.math.rwth-aachen.de)

Homepage: <http://wwwb.math.rwth-aachen.de/~daniel/>

Address: Daniel Robertz  
Lehrstuhl B fuer Mathematik, RWTH Aachen  
Templergraben 64  
52062 Aachen  
Germany

**Hans Schönemann**

Email: [hannes@mathematik.uni-kl.de](mailto:hannes@mathematik.uni-kl.de)

Homepage: <http://www.mathematik.uni-kl.de/~hannes/>

Address: Department of Mathematics  
University of Kaiserslautern  
67653 Kaiserslautern  
Germany

**Andreas Steenpaß**

Email: [steenpass@mathematik.uni-kl.de](mailto:steenpass@mathematik.uni-kl.de)

Address: Department of Mathematics  
University of Kaiserslautern  
67653 Kaiserslautern  
Germany

**Vinay Wagh**

Email: [waghoba@gmail.com](mailto:waghoba@gmail.com)

Homepage: <http://www.iitg.ernet.in/vinay.wagh/>

Address: E-102, Department of Mathematics,  
Indian Institute of Technology Guwahati,  
Guwahati, Assam, India.  
PIN: 781 039.  
India

## **Copyright**

© 2007-2015 by Mohamed Barakat, Simon Görtzen, Markus Kirschmer, Markus Lange-Hegermann, Oleksandr Motsak, Max Neunhöffer, Daniel Robertz, and Hans Schönemann. This package may be distributed under the terms and conditions of the GNU Public License Version 2 or (at your option) any later version.

# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Ring Constructions for Supported External Computer Algebra Systems . . . . .	4
<b>2</b>	<b>Installation of the <code>RingsForHomalg</code> Package</b>	<b>11</b>
<b>3</b>	<b>The Ring Table</b>	<b>12</b>
3.1	An Example for a Ring Table - Singular . . . . .	12
	<b>References</b>	<b>24</b>
	<b>Index</b>	<b>25</b>

# Chapter 1

## Introduction

This package is part of the `homalg` project [hom22]. The role of the package is described in the manual of the `homalg` package.

### 1.1 Ring Constructions for Supported External Computer Algebra Systems

Here are some of the supported ring constructions:

#### 1.1.1 external GAP

Example

```
gap> zz := HomalgRingOfIntegersInExternalGAP( );
Z
gap> Display( zz );
<An external ring residing in the CAS GAP>
gap> F2 := HomalgRingOfIntegersInExternalGAP( 2, zz );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS GAP>
```

`F2 := HomalgRingOfIntegersInExternalGAP( 2 )` would launch another GAP.

Example

```
gap> Z4 := HomalgRingOfIntegersInExternalGAP( 4, zz );
Z/4Z
gap> Display( Z4 );
<An external ring residing in the CAS GAP>
gap> Z_4 := HomalgRingOfIntegersInExternalGAP( zz ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInExternalGAP( zz );
Q
gap> Display( Q );
<An external ring residing in the CAS GAP>
```

## 1.1.2 Singular

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Singular ).stdout )
gap> F2 := HomalgRingOfIntegersInSingular( 2 );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Singular>
gap> F2s := HomalgRingOfIntegersInSingular( 2, "s", F2 );
GF(2)(s)
gap> Display( F2s );
<An external ring residing in the CAS Singular>
gap> zz := HomalgRingOfIntegersInSingular( F2 );
Z
gap> Display( zz );
<An external ring residing in the CAS Singular>
gap> Q := HomalgFieldOfRationalsInSingular( F2 );
Q
gap> Display( Q );
<An external ring residing in the CAS Singular>
gap> Qs := HomalgFieldOfRationalsInSingular( "s", F2 );
Q(s)
gap> Display( Qs );
<An external ring residing in the CAS Singular>
gap> Qi := HomalgFieldOfRationalsInSingular( "i", "i^2+1", Q );
Q[i]/(i^2+1)
gap> Display( Qi );
<An external ring residing in the CAS Singular>
#@fi
```

`Q := HomalgFieldOfRationalsInSingular( )` would launch another Singular.

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Singular ).stdout )
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS Singular>
gap> F2sxyz := F2s * "x,y,z";
GF(2)(s)[x,y,z]
gap> Display( F2sxyz );
<An external ring residing in the CAS Singular>
gap> F2xyzw := F2xyz * "w";
GF(2)[x,y,z][w]
gap> Display( F2xyzw );
<An external ring residing in the CAS Singular>
gap> F2sxyzw := F2sxyz * "w";
GF(2)(s)[x,y,z][w]
gap> Display( F2sxyzw );
<An external ring residing in the CAS Singular>
gap> zzxyz := zz * "x,y,z";
Z[x,y,z]
gap> Display( zzxyz );
<An external ring residing in the CAS Singular>
```

```

gap> zzxyzw := zzxyz * "w";
Z[x,y,z][w]
gap> Display( zzxyzw );
<An external ring residing in the CAS Singular>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS Singular>
gap> Qsxyz := Qs * "x,y,z";
Q(s)[x,y,z]
gap> Display( Qsxyz );
<An external ring residing in the CAS Singular>
gap> Qixyz := Qi * "x,y,z";
(Q[i]/(i^2+1))[x,y,z]
gap> Display( Qixyz );
<An external ring residing in the CAS Singular>
gap> Qxyzw := Qxyz * "w";
Q[x,y,z][w]
gap> Display( Qxyzw );
<An external ring residing in the CAS Singular>
gap> Qsxyzw := Qsxyz * "w";
Q(s)[x,y,z][w]
gap> Display( Qsxyzw );
<An external ring residing in the CAS Singular>
gap> Dxyz := RingOfDerivations( Qxyz, "Dx,Dy,Dz" );
Q[x,y,z]<Dx,Dy,Dz>
gap> Display( Dxyz );
<An external ring residing in the CAS Singular>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS Singular>
gap> Dsxyz := RingOfDerivations( Qsxyz, "Dx,Dy,Dz" );
Q(s)[x,y,z]<Dx,Dy,Dz>
gap> Display( Dsxyz );
<An external ring residing in the CAS Singular>
gap> Esxyz := ExteriorRing( Qsxyz, "e,f,g" );
Q(s){e,f,g}
gap> Display( Esxyz );
<An external ring residing in the CAS Singular>
gap> Dixyz := RingOfDerivations( Qixyz, "Dx,Dy,Dz" );
(Q[i]/(i^2+1))[x,y,z]<Dx,Dy,Dz>
gap> Display( Dixyz );
<An external ring residing in the CAS Singular>
gap> Eixyz := ExteriorRing( Qixyz, "e,f,g" );
(Q[i]/(i^2+1)){e,f,g}
gap> Display( Eixyz );
<An external ring residing in the CAS Singular>
gap> qring := HomalgQRingInSingular( Qxyz, "x*y" );
Q[x,y,z]/( x*y )
gap> Display( qring );
<An external ring residing in the CAS Singular>

```



```
gap> "z + x*y" / qring = "z" / qring;
true
#@fi
```

### 1.1.3 MAGMA

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_MAGMA ).stdout )
gap> zz := HomalgRingOfIntegersInMAGMA( );
Z
gap> Display( zz );
<An external ring residing in the CAS MAGMA>
gap> F2 := HomalgRingOfIntegersInMAGMA( 2, zz );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS MAGMA>
#@fi
```

F2 := HomalgRingOfIntegersInMAGMA( 2 ) would launch another MAGMA.

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_MAGMA ).stdout )
gap> Z_4 := HomalgRingOfIntegersInMAGMA( zz ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInMAGMA( zz );
Q
gap> Display( Q );
<An external ring residing in the CAS MAGMA>
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS MAGMA>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS MAGMA>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS MAGMA>
#@fi
```

### 1.1.4 Macaulay2

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Macaulay2 ).stdout )
gap> zz := HomalgRingOfIntegersInMacaulay2( );
Z
gap> Display( zz );
<An external ring residing in the CAS Macaulay2>
gap> F2 := HomalgRingOfIntegersInMacaulay2( 2, zz );
GF(2)
```

```
gap> Display( F2 );
<An external ring residing in the CAS Macaulay2>
#@fi
```

F2 := HomalgRingOfIntegersInMacaulay2( 2 ) would launch another Macaulay2.

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Macaulay2 ).stdout )
gap> Z_4 := HomalgRingOfIntegersInMacaulay2( zz ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInMacaulay2( zz );
Q
gap> Display( Q );
<An external ring residing in the CAS Macaulay2>
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS Macaulay2>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS Macaulay2>
gap> Dxyz := RingOfDerivations( Qxyz, "Dx,Dy,Dz" );
Q[x,y,z]<Dx,Dy,Dz>
gap> Display( Dxyz );
<An external ring residing in the CAS Macaulay2>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS Macaulay2>
#@fi
```

### 1.1.5 Sage

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Sage ).stdout )
gap> zz := HomalgRingOfIntegersInSage( );
Z
gap> Display( zz );
<An external ring residing in the CAS Sage>
gap> F2 := HomalgRingOfIntegersInSage( 2, zz );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Sage>
#@fi
```

F2 := HomalgRingOfIntegersInSage( 2 ) would launch another Sage.

Example

```
#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Sage ).stdout )
gap> Z_4 := HomalgRingOfIntegersInSage( zz ) / 4;
Z/( 4 )
```

```

gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInSage( zz );
Q
gap> Display( Q );
<An external ring residing in the CAS Sage>
gap> F2x := F2 * "x";
GF(2)[x]
gap> Display( F2x );
<An external ring residing in the CAS Sage>
gap> Qx := Q * "x";
Q[x]
gap> Display( Qx );
<An external ring residing in the CAS Sage>
#@fi

```

### 1.1.6 Maple

Example

```

#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Maple ).stdout )
gap> zz := HomalgRingOfIntegersInMaple( );
Z
gap> Display( zz );
<An external ring residing in the CAS Maple>
gap> F2 := HomalgRingOfIntegersInMaple( 2, zz );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Maple>
#@fi

```

F2 := HomalgRingOfIntegersInMaple( 2 ) would launch another Maple.

Example

```

#@if IsBound( TryLaunchCAS_IO_ForHomalg( HOMALG_IO_Maple ).stdout )
gap> Z4 := HomalgRingOfIntegersInMaple( 4, zz );
Z/4Z
gap> Display( Z4 );
<An external ring residing in the CAS Maple>
gap> Z_4 := HomalgRingOfIntegersInMaple( zz ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInMaple( zz );
Q
gap> Display( Q );
<An external ring residing in the CAS Maple>
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS Maple>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );

```

```
<An external ring residing in the CAS Maple>
gap> Dxyz := RingOfDerivations( Qxyz, "Dx,Dy,Dz" );
Q[x,y,z]<Dx,Dy,Dz>
gap> Display( Dxyz );
<An external ring residing in the CAS Maple>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS Maple>
#@fi
```

## Chapter 2

# Installation of the RingsForHomalg Package

To install this package just extract the package's archive file to the GAP pkg directory.

By default the RingsForHomalg package is not automatically loaded by GAP when it is installed. You must load the package with

```
LoadPackage( "RingsForHomalg" );
```

before its functions become available.

Please, send us an e-mail if you have any questions, remarks, suggestions, etc. concerning this package. Also, we would be pleased to hear about applications of this package.

The authors.

## Chapter 3

# The Ring Table

### 3.1 An Example for a Ring Table - Singular

todo: introductory text, mention: transposed matrices, the macros, refer to the philosophy

#### 3.1.1 BasisOfRowModule (in the homalg table for Singular)

▷ BasisOfRowModule( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro BasisOfRowModule (3.1.2) inside the computer algebra system.

Code

```
BasisOfRowModule :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NumberColumns( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = BasisOfRowModule(", M, ")" ],
    "need_command",
    "BasisOfModule"
  );

  return N;

end,
```

#### 3.1.2 BasisOfRowModule (Singular macro)

▷ BasisOfRowModule( $M$ ) (function)

**Returns:**

Code

```

BasisOfRowModule := "\n\
proc BasisOfRowModule (matrix M)\n\
{\n\
    return(std(M));\n\
}\n\n",

```

### 3.1.3 BasisOfColumnModule (in the homalg table for Singular)

▷ BasisOfColumnModule( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro BasisOfColumnModule (3.1.4) inside the computer algebra system.

Code

```

BasisOfColumnModule :=
function( M )
    local N;

    N := HomalgVoidMatrix(
        NumberRows( M ),
        "unknown_number_of_columns",
        HomalgRing( M )
    );

    homalgSendBlocking(
        [ "matrix ", N, " = BasisOfColumnModule(", M, ")" ],
        "need_command",
        "BasisOfModule"
    );

    return N;

end,

```

### 3.1.4 BasisOfColumnModule (Singular macro)

▷ BasisOfColumnModule( $M$ ) (function)

**Returns:**

Code

```

BasisOfColumnModule := "\n\
proc BasisOfColumnModule (matrix M)\n\
{\n\
    return(Involution(BasisOfRowModule(Involution(M))));\n\
}\n\n",

```

### 3.1.5 DecideZeroRows (in the homalg table for Singular)

▷ DecideZeroRows( $A$ ,  $B$ ) (function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `DecideZeroRows` (3.1.6) inside the computer algebra system. The rows of  $B$  must form a basis (see `BasisOfRowModule` (3.1.1)).

Code

```
DecideZeroRows :=
function( A, B )
  local N;

  N := HomalgVoidMatrix(
    NumberRows( A ),
    NumberColumns( A ),
    HomalgRing( A )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = DecideZeroRows(", A, B, ")" ],
    "need_command",
    "DecideZero"
  );

  return N;

end,
```

### 3.1.6 DecideZeroRows (Singular macro)

▷ `DecideZeroRows(A, B)`

(function)

**Returns:**

Code

```
DecideZeroRows := "\n\
proc DecideZeroRows (matrix A, module B)\n\
{\n\
  attrib(B,\"isSB\",1);\n\
  return(reduce(A,B));\n\
}\n\n",
```

### 3.1.7 DecideZeroColumns (in the homalg table for Singular)

▷ `DecideZeroColumns(A, B)`

(function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `DecideZeroColumns` (3.1.8) inside the computer algebra system. The columns of  $B$  must form a basis (see `BasisOfColumnModule` (3.1.3)).

Code

```
DecideZeroColumns :=
function( A, B )
  local N;

  N := HomalgVoidMatrix(
    NumberRows( A ),
```



```

    NumberColumns( A ),
    HomalgRing( A )
);

homalgSendBlocking(
  [ "matrix ", N, " = DecideZeroColumns(", A, B, ")" ],
  "need_command",
  "DecideZero"
);

return N;

end,
```

### 3.1.8 DecideZeroColumns (Singular macro)

▷ DecideZeroColumns( A, B)

(function)

**Returns:**

Code

```

DecideZeroColumns := "\n\
proc DecideZeroColumns (matrix A, matrix B)\n\
{\n\
  return(Involution(DecideZeroRows(Involution(A),Involution(B))));\n\
}\n\n",
```

### 3.1.9 SyzygiesGeneratorsOfRows (in the homalg table for Singular)

▷ SyzygiesGeneratorsOfRows( M)

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro SyzygiesGeneratorsOfRows (3.1.10) inside the computer algebra system.

Code

```

SyzygiesGeneratorsOfRows :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NumberRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = SyzygiesGeneratorsOfRows(", M, ")" ],
    "need_command",
    "SyzygiesGenerators"
  );

  return N;

end,
```

### 3.1.10 SyzygiesGeneratorsOfRows (Singular macro)

▷ SyzygiesGeneratorsOfRows( $M$ ) (function)

**Returns:**

```
Code
SyzygiesGeneratorsOfRows := "\n\
proc SyzygiesGeneratorsOfRows (matrix M)\n\
{\n\
  return(SyzForHomalg(M));\n\
}\n\n",
```

### 3.1.11 SyzygiesGeneratorsOfColumns (in the homalg table for Singular)

▷ SyzygiesGeneratorsOfColumns( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro SyzygiesGeneratorsOfColumns (3.1.12) inside the computer algebra system.

```
Code
SyzygiesGeneratorsOfColumns :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    NumberColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = SyzygiesGeneratorsOfColumns(", M, ")" ],
    "need_command",
    "SyzygiesGenerators"
  );

  return N;

end,
```

### 3.1.12 SyzygiesGeneratorsOfColumns (Singular macro)

▷ SyzygiesGeneratorsOfColumns( $M$ ) (function)

**Returns:**

```
Code
SyzygiesGeneratorsOfColumns := "\n\
proc SyzygiesGeneratorsOfColumns (matrix M)\n\
{\n\
  return(Involution(SyzForHomalg(Involution(M))));\n\
}\n\n",
```

### 3.1.13 BasisOfRowsCoeff (in the homalg table for Singular)

▷ `BasisOfRowsCoeff(M, T)` (function)

#### Returns:

This is the entry of the `homalg` table, which calls the corresponding macro `BasisOfRowsCoeff` (3.1.14) inside the computer algebra system.

```
Code
BasisOfRowsCoeff :=
function( M, T )
  local v, N;

  v := homalgStream( HomalgRing( M ) )!.variable_name;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NumberColumns( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, T, " = BasisOfRowsCoeff(", M, ")" ],
    "need_command",
    "BasisCoeff"
  );

  return N;

end,
```

### 3.1.14 BasisOfRowsCoeff (Singular macro)

▷ `BasisOfRowsCoeff(M, T)` (function)

#### Returns:

```
Code
BasisOfRowsCoeff := ""
proc BasisOfRowsCoeff (matrix M)
{
  matrix B = BasisOfRowModule(M);
  option(noredSB);
  matrix T = lift(M,B);
  option(redSB);
  return(B,T);
}

"" ,
```

### 3.1.15 BasisOfColumnsCoeff (in the homalg table for Singular)

▷ `BasisOfColumnsCoeff(M, T)` (function)

#### Returns:

This is the entry of the `homalg` table, which calls the corresponding macro `BasisOfColumnsCoeff` (3.1.16) inside the computer algebra system.

Code

```

BasisOfColumnsCoeff :=
function( M, T )
  local v, N;

  v := homalgStream( HomalgRing( M ) )!.variable_name;

  N := HomalgVoidMatrix(
    NumberRows( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, T, " = BasisOfColumnsCoeff(", M, ")" ],
    "need_command",
    "BasisCoeff"
  );

  return N;

end,

```

### 3.1.16 BasisOfColumnsCoeff (Singular macro)

▷ `BasisOfColumnsCoeff(M, T)`

(function)

**Returns:**

Code

```

BasisOfColumnsCoeff := ""
proc BasisOfColumnsCoeff (matrix M)
{
  matrix B,T = BasisOfRowsCoeff(Involution(M));
  return(Involution(B),Involution(T));
}

"",

```

### 3.1.17 DecideZeroRowsEffectively (in the homalg table for Singular)

▷ `DecideZeroRowsEffectively(A, B, T)`

(function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `DecideZeroRowsEffectively` (3.1.18) inside the computer algebra system. The rows of  $B$  must form a basis (see `BasisOfRowModule` (3.1.1)).

Code

```

DecideZeroRowsEffectively :=
function( A, B, T )
  local v, N;

```

```

v := homalgStream( HomalgRing( A ) )!.variable_name;

N := HomalgVoidMatrix(
  NumberRows( A ),
  NumberColumns( A ),
  HomalgRing( A )
);

homalgSendBlocking(
  [ "matrix ", N, T, " = DecideZeroRowsEffectively(", A, B, ")" ],
  "need_command",
  "DecideZeroEffectively"
);

return N;

end,

```

### 3.1.18 DecideZeroRowsEffectively (Singular macro)

▷ DecideZeroRowsEffectively(*A*, *B*, *T*)

(function)

**Returns:**

Code

```

DecideZeroRowsEffectively := ""
proc DecideZeroRowsEffectively (matrix A, module B)
{
  attrib(B,"isSB",1);
  matrix M = reduce(A,B);
  matrix T = lift(B,M-A);
  return(M,T);
}

"" ,

```

### 3.1.19 DecideZeroColumnsEffectively (in the homalg table for Singular)

▷ DecideZeroColumnsEffectively(*A*, *B*, *T*)

(function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `DecideZeroColumnsEffectively` (3.1.20) inside the computer algebra system. The columns of *B* must form a basis (see `BasisOfColumnModule` (3.1.3)).

Code

```

DecideZeroColumnsEffectively :=
function( A, B, T )
  local v, N;

  v := homalgStream( HomalgRing( A ) )!.variable_name;

  N := HomalgVoidMatrix(
    NumberRows( A ),
    NumberColumns( A ),

```

```

    HomalgRing( A )
);

homalgSendBlocking(
  [ "matrix ", N, T, " = DecideZeroColumnsEffectively(", A, B, ")" ],
  "need_command",
  "DecideZeroEffectively"
);

return N;

end,

```

### 3.1.20 DecideZeroColumnsEffectively (Singular macro)

▷ DecideZeroColumnsEffectively(*A*, *B*, *T*) (function)

**Returns:**

```

Code
DecideZeroColumnsEffectively := ""
proc DecideZeroColumnsEffectively (matrix A, matrix B)
{
  matrix M,T = DecideZeroRowsEffectively(Involution(A),Involution(B));
  return(Involution(M),Involution(T));
}

"" ,

```

### 3.1.21 RelativeSyzygiesGeneratorsOfRows (in the homalg table for Singular)

▷ RelativeSyzygiesGeneratorsOfRows(*M*, *M2*) (function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `RelativeSyzygiesGeneratorsOfRows` (3.1.22) inside the computer algebra system.

```

Code
RelativeSyzygiesGeneratorsOfRows :=
function( M, M2 )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NumberRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = RelativeSyzygiesGeneratorsOfRows(", M, M2, ")" ],
    "need_command",
    "SyzygiesGenerators"
  );

  return N;

```

```
end,
```

### 3.1.22 RelativeSyzygiesGeneratorsOfRows (Singular macro)

▷ RelativeSyzygiesGeneratorsOfRows( $M$ ,  $M2$ ) (function)

**Returns:**

```
Code
RelativeSyzygiesGeneratorsOfRows := "\n\
proc RelativeSyzygiesGeneratorsOfRows (matrix M1, matrix M2)\n\
{\n\
  return(modulo(M1, M2));\n\
}\n\n",
```

### 3.1.23 RelativeSyzygiesGeneratorsOfColumns (in the homalg table for Singular)

▷ RelativeSyzygiesGeneratorsOfColumns( $M$ ,  $M2$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro RelativeSyzygiesGeneratorsOfColumns (3.1.24) inside the computer algebra system.

```
Code
RelativeSyzygiesGeneratorsOfColumns :=
function( M, M2 )
  local N;

  N := HomalgVoidMatrix(
    NumberColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = RelativeSyzygiesGeneratorsOfColumns(", M, M2, ")" ],
    "need_command",
    "SyzygiesGenerators"
  );

  return N;

end,
```

### 3.1.24 RelativeSyzygiesGeneratorsOfColumns (Singular macro)

▷ RelativeSyzygiesGeneratorsOfColumns( $M$ ,  $M2$ ) (function)

**Returns:**

```
Code
RelativeSyzygiesGeneratorsOfColumns := "\n\
proc RelativeSyzygiesGeneratorsOfColumns (matrix M1, matrix M2)\n\
{\n\
```

```
return(Involution(RelativeSyzygiesGeneratorsOfRows(Involution(M1),Involution(M2)))));\n\
}\n\n",
```

### 3.1.25 ReducedSyzygiesGeneratorsOfRows (in the homalg table for Singular)

▷ ReducedSyzygiesGeneratorsOfRows( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro ReducedSyzygiesGeneratorsOfRows (3.1.26) inside the computer algebra system.

Code

```
ReducedSyzygiesGeneratorsOfRows :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NumberRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = ReducedSyzygiesGeneratorsOfRows(", M, ")" ],
    "need_command",
    "SyzygiesGenerators"
  );

  return N;

end,
```

### 3.1.26 ReducedSyzygiesGeneratorsOfRows (Singular macro)

▷ ReducedSyzygiesGeneratorsOfRows( $M$ ) (function)

**Returns:**

Code

```
ReducedSyzForHomalg := "\n\
proc ReducedSyzForHomalg (matrix M)\n\
{\n\
  return(matrix(nres(M,2)[2]));\n\
}\n\n",

ReducedSyzygiesGeneratorsOfRows := "\n\
proc ReducedSyzygiesGeneratorsOfRows (matrix M)\n\
{\n\
  return(ReducedSyzForHomalg(M));\n\
}\n\n",
```

### 3.1.27 ReducedSyzygiesGeneratorsOfColumns (in the homalg table for Singular)

▷ ReducedSyzygiesGeneratorsOfColumns( $M$ ) (function)

**Returns:**



This is the entry of the `homalg` table, which calls the corresponding macro `ReducedSyzygiesGeneratorsOfColumns` (3.1.28) inside the computer algebra system.

Code

```

ReducedSyzygiesGeneratorsOfColumns :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    NumberColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = ReducedSyzygiesGeneratorsOfColumns(", M, ")" ],
    "need_command",
    "SyzygiesGenerators"
  );

  return N;

end,

```

### 3.1.28 ReducedSyzygiesGeneratorsOfColumns (Singular macro)

▷ `ReducedSyzygiesGeneratorsOfColumns(M)`

(function)

**Returns:**

Code

```

ReducedSyzygiesGeneratorsOfColumns := "\n\
proc ReducedSyzygiesGeneratorsOfColumns (matrix M)\n\
{\n\
  return(Involution(ReducedSyzForHomalg(Involution(M))));\n\
}\n\n",

```

# References

[hom22] homalg project authors. The homalg project – Algorithmic Homological Algebra. ([https://homalg-project.github.io/prj/homalg\\_project](https://homalg-project.github.io/prj/homalg_project)), 2003–2022. 4

# Index

RingsForHomalg, 4

BasisOfColumnModule

in the homalg table for Singular, 13

Singular macro, 13

BasisOfColumnsCoeff

in the homalg table for Singular, 17

Singular macro, 18

BasisOfRowModule

in the homalg table for Singular, 12

Singular macro, 12

BasisOfRowsCoeff

in the homalg table for Singular, 17

Singular macro, 17

DecideZeroColumns

in the homalg table for Singular, 14

Singular macro, 15

DecideZeroColumnsEffectively

in the homalg table for Singular, 19

Singular macro, 20

DecideZeroRows

in the homalg table for Singular, 13

Singular macro, 14

DecideZeroRowsEffectively

in the homalg table for Singular, 18

Singular macro, 19

ReducedSyzygiesGeneratorsOfColumns

in the homalg table for Singular, 22

Singular macro, 23

ReducedSyzygiesGeneratorsOfRows

in the homalg table for Singular, 22

Singular macro, 22

RelativeSyzygiesGeneratorsOfColumns

in the homalg table for Singular, 21

Singular macro, 21

RelativeSyzygiesGeneratorsOfRows

in the homalg table for Singular, 20

Singular macro, 21

SyzygiesGeneratorsOfColumns

in the homalg table for Singular, 16

Singular macro, 16

SyzygiesGeneratorsOfRows

in the homalg table for Singular, 15

Singular macro, 16